

Micro Adjust

Push-Pull Control Head



Description:

Micro Adjust
Industrial Push-Pull
Control Head

Applications:

- Throttle control
- Regulating valve

Features:

- Load: 20lb maximum
- Travel: 3.00" maximum
- Threaded mount
- Friction lock
- Disconnect

Other Related Products:

- Twist Lock
- Non Lock

Control Head Industrial

Micro Adjust control heads are ideal for remote operation of a throttle, regulating valve, or other applications needing precise adjustment capabilities. Depressing the center button allows pushing or pulling the knob to make course travel adjustments. A flexible dust seal protects the internal release mechanism. Rotating the knob clockwise extends the output in the finite mode, and counter-clockwise retracts. Four and one-half turns results in 1" of linear travel. The maximum recommended load is 20lbs. Normal vibration does not affect the micro adjust setting. An optional friction lock accessory is available for applications where vibration is excessive. A disconnect feature and various output end configurations are available to suit a particular application. The ordering code and technical description show these choices.



Micro Adjust


Material

- Plated Carbon Steel Corrosion-Proof Control Heads

Suggested End Fittings

- See Hardware/End Fittings or Call Factory for More Information

All line art dimensions are represented in inches



Control Head Matrix

	Extended Dimensions	Non Lock VLD	Non Lock LD	Twist Lock	Micro Adjust	
<p>VLD</p>	"A" EXTENDED	81V32	51V32	21V32DF		EXT
	1" 4.94"	81V42	51V42	21V42DF		
	2" 6.94"	86V32	56V32	26V32DF		UTL
	3" 8.94"	86V42	56V42	26V42DF		
<p>VLD</p>	"A" EXTENDED	81V33	51V33	21V33DF		EXT
	1" 4.25"	81V43	51V43	21V43DF		
	2" 6.25"	86V33	56V33	26V33DF		UTL
	3" 8.25"	86V43	56V43	26V43DF		
<p>LD</p>	"A" EXTENDED		91L32	51L32	21L32DF	EXT
	1" 5.18"		91L42	51L42	21L42DF	
	2" 7.18"		96L32	56L32	26L32DF	UTL
	3" 9.18"		96L42	56L42	26L42DF	
<p>LD</p>	"A" EXTENDED		91L33	51L33	21L33DF	
	1" 4.56"		91L43	51L43	21L43DF	
	2" 6.56"		96L33	56L33	26L33DF	
	3" 8.56"		96L43	56L43	26L43DF	
<p>VLD</p>	L	79V00	59V00	29V00		BRIS
	12.00	79V04	59V04	29V04		
	1.75	79V05	59V05	29V05		
	.38					
<p>LD</p>	L					
	1.41					
	1.92					
	1.00					

Linking Motion & Control...
The Tuthill Solution



Cablecraft® Ordering Codes

2 - 1 - L - 3 - 2 - DF - (6) - 3 - 120

Control Head Type — 2 = Micro Adjust

Cable Type — 1 = Low Friction-EXT 3 = Low Friction 6 = Utility 9 = Bristow

Cable Size — V = Very Light Duty L = Light Duty

Stainless Steel Options — 0 = Carbon Steel Fittings
3 = with Stainless Steel End Rod
4 = with Stainless Steel End Rod, Support Tube and Innermember Armor

Output End Fittings — 0 = See Illustration 2 = Threaded Swivel 3 = Grooved Swivel

Cable Options — D = Disconnect Feature F = Friction Lock Assembly

Seal Options (Use This Number Only if Requesting Optional Seals) — 5 = Improved Model 5 Wiper Seal is Standard on Low Friction-EXT & Utility
6 = Model 6 Wiper Seal, Optional on All Controls

Cable Travel — 1" - 3" (For Output Fittings Style 2 & 3 Only)

Overall Length — (See Overall Length Dimension Points Indicated on Each Illustration)

* Please refer to the cautions/warnings and appropriate installation usage information in the Technical/Application Data sheet
* For application assistance/technical questions, please contact us at the appropriate location listed below or through our website at www.tuthillcontrols.com



4401 South Orchard Street
Tacoma, Washington 98466 USA
Tel 253 475-1080 Fax 253 474-1623

2110 Summit Street
New Haven, Indiana USA 46774
Tel 260 749-5105 Fax 260 493-2387
www.tuthillcontrols.com

Diplocks Way-South Road
Hailsham, East Sussex BN27 3JF, England
Tel 44 1323 841510 Fax 44 1323 845848

Hingbergstrasse 79
45468 Mulheim an Der Rhur, Germany
Tel 49-208-300-650 Fax 49-208-300-6550